

Product				
	Kamvas Pro 16 Plus (4K) Buy >	Kamvas Pro 24(4K) Buy >	Kamvas 24 Plus Buy >	Kamvas RDS-160 Buy >
Appearance				
Color	Dark Grey	Black	Dark Gray	Cosmo Black, Metal Gray
Dimension	402.7 x 257.4 x 13mm	589.2 x 364 x 22.7mm	604.2 x 358 x 21~28.3mm (Without Stand)	423.5 x 253 x 12mm
Workspace	345.6 x 194.4mm	527.04 x 296.46mm	526.85 x 296.35mm	344.16 x 193.6mm
Net Weight	1.27Kg	6.3Kg	5.6Kg (With Stand)	1.26Kg
Touch	-	-	-	-
Stand	Foldable Stand ST200 20°/45°	Integrated Stand 20°	Adjustable Stand 20°~80°	Foldable Stand ST300 20°/45°
Video Interface	USB-C, Full-Featured USB-C	HDMI, DP, USB-C, DC, USB-A 2.0 x 2, 3.5mm headphone jack	USB-C, Full-Featured USB-C	3-in-1 USB-C(HDMI), Full Featured USB-C
Screen				
Resolution	3840 x 2160 (16:9) UHD	3840 x 2160(16:9) UHD	2560 x 1440 (16:9) QHD	1920 x 1080 (16:9)
LCD Type	IPS	IPS	IPS	IPS
AG Glass	Anti-glare etched glass	Anti-glare etched glass	Anti-glare etched glass	Anti-glare etched glass
Full Lamination	YES	YES	Full Lamination	Full lamination
Contrast Ratio	1200:1	1200:1	1200:1	1000:1
Brightness	200cd/m2 (Max.)	220cd/m ² (Max.)	220cd/m ² (Max.)	220nit (Max.)
Response Time	25ms	10ms	14ms	25ms
Viewing Angle	89°/89°(H)/89°/89°(V) (Typ.)(CR > 10)	89°/89°(H)/89°/89°(V) (Typ.)(CR > 10)	89°/89°(H)/89°/89°(V) (Typ.)(CR > 10)	89°/89°(H)/89°/89°(V) (Typ.)(CR > 10)
Gamut	145% sRGB(Quantum dots)	140% sRGB	97%NTSC/140% sRGB	145% sRGB(Quantum dots)
Display Color	16.7M(8bit)	1.07B(10bit)	16.7M (8bit)	16.7M(8bit)
Technical Specifications				
Digital Pen	PW517	PW517	PW517	PW517
Pen Technology	Battery-Free Electromagnetic Resonance	Battery-Free Electromagnetic Resonance	Battery-Free Electromagnetic Resonance	Battery-free EMR
Pen Resolution	5080LPI	5080LPI	5080 LPI	5080 LPI
Pressure Sensitivity	8192Levels	8192Levels	8192Levels	8192levels
Tilt Support	±60°	±60°	±60°	±60°
Sensing Height	10mm	10mm	10mm	10mm
Report Rate	> 220PPS	> 300PPS	> 220PPS	> 220PPS
Accuracy	±0.3mm (center) ±2mm (corner)	±0.3mm(center) ±3mm(corner)	±0.3mm (Center) ±2mm (Corner)	±0.3mm(Center)±2mm(Corner)
Press Keys	-	-	-	10 programmable press keys
Operating Conditions				
Input Voltage	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz	USB 5V
Output Voltage	5V 3A	19V 3A	19V 3A	5V 2A
Power Consumption	≤15W	≤35W	≤20W	≤10W
Standby Consumption	≤0.3W	≤0.4W	≤0.3W	≤0.3W
Working Temp. and Humidity	0-40°C、20-80%	0-40°C. 20-80%	0-40°C、20-80%	0-40°C, 20-80%
Storage Temp. and Humidity	-20°C~60°C、10-90%	-20°C~60°C. 10-90%	-20°C~60°C, 10-90%	-20°C~60°C, 10-90%
OS Compatibility				
OS Compatibility	Windows 7 or later macOS 10.12 or later Android (USB3.1 DP1.2) Linux	Windows 7 or later macOS 10.12 or later Android(USB3.1 DP1.2 or later) Linux	Windows 7 or later, macOS 10.12 or later, Android(USB3.1 DP1.2 or later) Linux	Windows 7 or later, macOS 10.12 or later, Android (USB 3.1 DP1.2)
Model				
Model	GT1562	GT2401	GS2402	RDS-160